

SAFETY PRECAUTIONS

Read all safety precautions and installation instructions carefully before installing theLightCage®. Failure to comply with these instructions could result in potentially fatal electric shock and or property damage.

If a ladder is required for installation, make sure to follow all safety precautions stated by the ladder manufacturer.

Do not handle an energized fixture or attempt to energize any fixture with wet hands or while standing on a wet or damp surface, or in water.

ASSEMBLY INSTRUCTIONS

NOTE: Do not clasp the two halves of the LightCage together prior to installation.

1. If attached together prior to installation, separate the halves by gently lifting the molded plastic clamp with pliers, while pulling the halves apart. Once the cage half is released from the clamp, the halves will easily lift off the connecting rods.
2. Insure that electrical power is turned off before installing theLightCage.
3. Using a screw driver, loosen the two (2) screws that secure the light fixture to the electrical box so that approximately a ¼ inch gap is visible between the light fixture and the electrical box (see figure 1). If screws are too short, replace with longer screws of the same type.
4. Slide each LightCage half between the light fixture and the electrical box (see figure 2).
5. Clasp both halves of the LightCage together until you feel or hear a “snap” and the two halves are flush together everywhere (you can use a pliers or other gripping tool if necessary), (see figure 3).
6. Tighten the screws that were loosened in step 2. **Note: Do not over tighten the screws as they may strip off or break.**
7. Restore power to the light




Figure 1




Figure 2




Figure 3